

MZR02 SERIES

Fingerprint Smart Card Reader



Get Fingerprint Scanner and secure contact ISO/IEC 7816 and contactless 13.56 MHz technologies in one device.

MZR02 is the ideal combination of fingerprint sensor, contact, contactless, and near field communication (NFC) technologies. Supporting fingerprint biometrics, ISO/IEC 7816 contact cards, 13.56 MHz contactless technology, and NFC, this PC-linked Fingerprint Dual Interface Reader is suitable for any smart card application where multifactor authentication is needed for higher security without sacrificing convenience.

MZR02 is built with an ultra-thin press-type optical single-finger fingerprint module, using patented and patent-pending fingerprint technology. It has the characteristics of low power consumption, high sensitivity and high signal-to-noise ratio.

It can realize two-way fingerprint entry and comparison, and perfectly analyze touch and incomplete fingerprints in various dry and wet environments. Complies with FBI PIV-071006, Mobile ID FAP 20 standards..

With its all-in-one concept, this multi-function device of international standard protocol can be easily connected to PC and mobile portable terminal. It is widely used in various information security fields such as secure identity authentication, PKI key authentication, fingerprint data collection, digital signature authentication, identity certificate issuance, etc.

Features:

- User Convenience, ergonomic design
- Compliant with PC/SC, CCID Standards
- Supports ISO/IEC 7816 Part 1 to 4
- Supports ISO/IEC14443, ISO/IEC18092
- Supports Windows, Android, Linux
- FBI PIV-071006, Mobile ID FAP 20
- High-quality fingerprint image
- Dynamic fingerprint detection
- High-speed image acquisition
- Logo, case color, and shell surface treatment process customizable

* The fingerprint sensor can be customized to Suprema BM-SLIM2 *

| | MRZ02 | MZR02-SCR |
|------------------|-------|-----------|
| Contact card | ✓ | ✓ |
| Contactless card | ✓ | X |
| Fingerprint | ✓ | ✓ |

| Parameter | Details |
|---|--|
| Host Interface | USB 2.0 CCID (USB 1.1/3.0 compliant) |
| Communication Speed | 12 Mbps (USB 2.0 full speed) |
| Fingerprint Sensor | |
| Collection window area | 16.4 mm * 21.1mm |
| Collection effective area | 15.24mm * 20.32mm |
| Sensor resolution | 500 DPI±1% |
| Sensor pixel area | 300 * 400 pixels |
| Image dynamic range | 210 levels |
| Grayscale image | 8-bit, 256 levels of gray |
| Image frame rate | 30 frame/Sec |
| SDK development kit | C++, JAVA |
| Contact Smart Card Interface | |
| Supported Standards | ISO/IEC 7816 Part 1 to 4 ,classes A/B/C (5V, 3.3V, 1.8V) |
| Contact Smart Card Protocols | T=0, T=1; |
| Smart Card Interface Speed | Up to 600 kbps (depending on card) , TA1=97 |
| Smart Card Clock Frequency | ISO/IEC 7816 compliant up to 5 MHz; Operates up to 12 MHz |
| Smart Card Detection | Card present switch; Automatic power on/off; Short circuit protection |
| Contact Card Slot | ID-1 Sliding Contact Socket (8 pin) |
| Contactless Smart Card Interface | |
| Supported Contactless Standards | ISO/IEC 14443 A&B, ISO/IEC18092 |
| Protocols | T=CL |
| Supported Contactless Card ICs | MIFARE® Classic Family, MIFARE Ultralight Family, MIFARE Plus Family, MIFARE DESFire Family, FeliCa™, NFC Forum Tag types 1/2/3/4 |
| Data Transfer Rate | 106/212/424/848 kbits/s, depending on card IC |
| Driver and Software | |
| PC/SC Driver | PC/SC Specification Ver. 2.01.14 for: <ul style="list-style-type: none"> Windows® 7/8/10/11 (32 and 64 bit), Windows® Server 2008/2012/2016/2019, WindowsXP, Linux 2.6.x, and 3.x, 4.x, 5.x (32 and 64 bit), Android 4.0 and higher |
| Software | PC/SC API; CT-API (through wrapper on top of PC/SC); M-Card API (through wrapper on top of PC/SC) |
| Operating Conditions | |
| Power Supply | USB Bus-powered |
| Power Consumption | <220 mA, excluding smart card; < 400 mA, with smart card; < 600 µA in Standby Mode |
| Dimensions(L x W x H) | 102.5 x 67 x 29.5 mm |
| Weight | 195 g ± 5% |
| Operating Temperature Range | 0° to 50° C (32° to 122° F) |
| Storage Temperature Range | -25° to 85° C (-13° to 185° F) |
| Operating Humidity Range | Up to 95% RH non-condensing |
| Connector | 1.5m USB cable with USB type A connector |
| Status Indicator | Dual color LED |
| Firmware | SmartOS™ |
| Firmware In-Field Upgradeable | Yes |
| Certifications / Compliance | |
| Systems/Standards | ISO/IEC 7816, ISO/IEC 14443, USB 2.0 Full Speed, CCID, Microsoft® WHQL,FBI PIV-071006, Mobile ID FAP 20 |
| Regulatory/Environmental | CE, RoHS |